



## DECLARATION OF PERFORMANCE

No. 016 DURO-CPR-7-2013 : DUROTOP

1. Unique identification code of the product:  
**016**
2. Intended uses:  
**EN 13813: Dry shake surface hardener for industrial floors**
3. Manufacturer:  
**DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, [www.durostick.gr](http://www.durostick.gr)**
4. Authorized representative:-
5. System of AVCP (assessment and verification of constancy of performance):  
**System 4**
- 6a. Harmonized standard:  
**EN 13813:2002**  
Notified body: -
- 6b. European Assessment Document **not applicable**      European Technical Assessment **not applicable**  
Technical Assessment Body **not applicable**      Notified Body **not applicable**

7. Declared performance

Essential characteristics	Performance	Test method
Reaction to fire	A <sub>1</sub> fl	EN 13501-1
Release of corrosive substances	CT	
Water permeability	NPD	EN 1062-3
Water vapour permeability	NPD	EN 12086
Compressive strength	C70	EN 13892-2
Flexural strength	F8	EN 13892-2
Wear resistance, BCA	BCA: AR1	EN 13892-4
Sound insulation/ Sound absorption	NPD*	EN ISO 140-6/ EN 12354-6
Thermal resistance/chemical resistance	NPD	EN 12664/ EN13529

\* NPD: No performance determined

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not applicable**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Evdoxia Kafritsa  
 Function: Head of R&D, QC Mortars Dept.  
 Place/Date: Aspropyrgos/ 2<sup>nd</sup> of January 2019

**CE MARKING ACCORDING TO CPR 305/2011 AND EN 13813:2002**



**DUROSTICK S.A**  
**ASPROPYRGOS ATHENS PC: 19300**  
**GREECE**  
**12**

**DoP No. : 016**  
**EN 13813 CT-C70-F8-AR1**

**DUROTOP**

**Cementitious screed material for use**  
**internally in buildings**

<b>Reaction to fire:</b>	<b>A1<sub>fl</sub></b>
<b>Release of corrosive substances:</b>	<b>CT</b>
<b>Water permeability:</b>	<b>NPD</b>
<b>Water vapour permeability:</b>	<b>NPD</b>
<b>Compressive strength:</b>	<b>C70</b>
<b>Flexural strength:</b>	<b>F8</b>
<b>Wear resistance, BCA:</b>	<b>AR1</b>
<b>Sound insulation/ Sound absorption:</b>	<b>NPD</b>
<b>Thermal resistance/chemical resistance:</b>	<b>NPD</b>

*The CE marking shown in this Declaration of Performance is the most recent, in accordance with the current regulation. Possible variations of the present marking with the corresponding one appearing on the packaging or the Technical Data Sheet may be due to the following reasons:*

- The packaging was already printed before the latest CE revision.*
- Printing error*
- Differences due to packaging sizes and printing method.*