

DUROSTICK FAST CLEAN



Fireplace & barbeque cleaner



PROPERTIES

Powerful active cleaner. It removes stubborn stains of soot, coal, dry or burnt fat and melted wax, just by spraying, without the need to scrub the surfaces. It restores the lost luster of the surfaces on which it is applied.

APPLICATIONS

DUROSTICK FAST CLEAN is ideal for both commercial and residential use on grills and barbeques, ovens and fireplaces lined with fire bricks or cast iron. Avoid the contact of the product or its vapours, with painted surfaces as well as ones made of aluminum, copper or brass as its powerful formula might damage those surfaces. Avoid cleaning artificial decorative stones. The product is suitable for cleaning natural stones and fire bricks.

USE

DUROSTICK QUICK CLEANER is a very powerful cleaning agent. During application and rins-

ing, the use of protective plastic gloves, is recommended. Spray from a distance of 20- 25cm and allow for the product act for 5 minutes. Subsequently, rinse using a wet sponge and plenty of water. On surfaces with persistent stains, repeat the process. Once all surfaces are thoroughly cleaned, rinsed and fully dried, the use of D-22, the water and oil repelling agent of DUROSTICK, is highly recommended. Protect decorative natural stones around the firebox or the barbeque from absorbing oil and grease.

STORAGE

Store in shaded places, for at least 36 months from production date.

SAFETY DIRECTIONS

The product is classified as corrosive. It is recommended to keep it locked, away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet

DUROSTICK FAST CLEAN



Fireplace & barbeque cleaner

PACKAGING

Carton box with 18 pcs of 750ml each one
5lt container (special order)

TECHNICAL SPECIFICATIONS	
Form - Clear	Corrosive liquid - Light yellow
Density	1.05±0.05kg/lt
Scent	Lemon
pH	12.5-13.5
It contains sodium hydroxide and includes anionic, amphoteric surfactants less than 5% and phosphonates less than 5%	
General Chemical State Laboratory Reg. No. 9281/0/2005	
Permit No. by State Chem. ELEFSIS: 3093/2008	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.