# DUROSTICK SILICONE SPRAY



Silicone based lubricant



## **PROPERTIES**

Clean lubricant that does not harden over time. It provides high waterproofing and nonstick/release properties. It is durable to high and low temperatures, oxidation and corrosion. It does not attract dust nor does it leave stains. It maintains rubber parts in good condition and does not allow them to freeze, dry or wear out. Prevents sticking, seizing, and the cricking sounds caused by surface friction.

#### **APPLICATIONS**

The SILICONE SPRAY of DUROSTICK is necessary for the smooth operation of sliding car sunroofs car seat rails and drawer slides etc. Suitable as a release agent for plastic and metal parts from their formwork. Protects inflatable boats from salt, as well as the boat fenders. It prevents materials sticking to conveyors, troughing idles, guides and pulleys.

It waterproofs surfaces like awning fabrics, umbrellas, tents and boat awnings made of canvas.

It removes moisture and forms a water repellent membrane on electrical cable contacts, relay switches, outboard engines as well as car and motorcycle engines. Necessary during electrical installations for the easy feeding of electrical wiring through conduits.

#### **USE**

Shake well before use. On clean surfaces, free of dust and dirt, spray evenly from 20-30cm away. Remove any excess product using a soft cloth.

#### **STORAGE**

Store in cool and shaded places, for at least 36 months from production date.

### **SAFETY DIRECTIONS**

The product is classified as extremely flammable. It is recommended to keep away from the reach of children. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

# DUROSTICK SILICONE SPRAY



Silicone based lubricant

## **PACKAGING**

Carton box with 12 pcs of 400ml each one

TECHNICAL SPECIFICATIONS	
Form - Color	Low viscosity liquid -
	Transparent
Density	0.60±0.05kg/lt

### **DUROSTICK S.A.**

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612 THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com