



DECLARATION OF PERFORMANCE

No. 001 DURO-CPR-7-2013 : SPECIAL MONOCOTTURA

1. Unique identification code of the product:
001
2. Intended uses:
EN 12004: Normal setting cementitious tile adhesive, C1. Internal wall and floor tiling.
3. Manufacturer:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, www.durostick.gr
4. Authorized representative:-
5. System of AVCP (assessment and verification of constancy of performance):
System 3
- 6a. Harmonized standard:
EN 12004:2007+A1:2012
Notified body:
The laboratory MITREC , notified body NB 0437, performed Initial testing under system 3 and issued test report No. 3351
- 6b. European Assessment Document **not applicable** European Technical Assessment **not applicable**
Technical Assessment Body **not applicable** Notified Body **not applicable**
7. Declared performance

Essential characteristics	Performance	Test method/Harmonised Standard	
Reaction to fire	Class A1WT*		
Bond strength as:		EN 1348 8.2	EN12004:2007 +A1:2012
• Initial tensile adhesion strength	≥ 0,50N/mm ²		
Durability of bond expresses as:			
• heat ageing	≥ 0,50N/mm	EN 1348 8.4	
• water immersion	≥ 0,50N/mm	EN 1348 8.3	
• freeze-thaw cycles	≥ 0,50N/mm	EN 1348 8.5	

**without need for testing*

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not applicable**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Evdoxia Kafritsa
 Function: Head of R&D, QC Mortars Dept.
 Place/Date: Aspropyrgos/ 8th of August 2017

CE MARKING ACCORDING TO CPR 305/2011 AND EN 12004:2007+A1:2012

	
DUROSTICK S.A	
ASPROPYRGOS ATHENS PC: 19300	
GREECE	
07	
DoP No.: 001	
EN 12004:2007+A1:2012	
SPECIAL MONOCOTTURA	
C1	
Normal setting cementitious adhesive	
Internal wall and floor tiling	
- Reaction to fire:	Class A1WT*
- Release of dangerous substances:	see MSDS
Bond Strength as:	
- Initial tensile adhesion strength :	≥0.50 N/mm²
Durability of bond expressed as :	
- Tensile adhesion strength after heat ageing:	≥0.50 N/mm²
- Tensile adhesion strength after water immersion:	≥0.50 N/mm²
- Tensile adhesion strength after freeze-thaw cycles	≥0.50 N/mm²

**without need for testing*

The CE marking shown in this Declaration of Performance is the most recent, in accordance with the current regulation. Possible variations of the present marking with the corresponding one appearing on the packaging or the Technical Data Sheet may be due to the following reasons:

- The packaging was already printed before the latest CE revision.*
- Printing error*
- Differences due to packaging sizes and printing method.*