DUROSTICK YACHT CLEANER



Strong cleaner for boats with active ingredients



PROPERTIES

Active and low foaming, alkaline cleaning agent that removes persistent stains from oils and grease, grime and soot. With just one spray, it removes ink from cuttlefish and squid (often occurrence when seagulls soil boat decks with ink while eating them), even when it penetrated through the pores of the surface. Removes hard sediment and microorganisms from boat hulls as well as seagull waste.

APPLICATIONS

DUROSTICK YACHT CLEANER is necessary for the general plastic boat cleaning. It revives and restores the original bright white color of gel coat. It deeply cleans and removes scum, black spots and yellow stains from upholstery and boat fenders as well. Ideal for cleaning lavatories and showers, faucets and sinks as well as plastic tables, chairs and tarps.

USE

DUROSTICK YACHT CLEANER is a very powerful cleaning agent. During application and even rinsing, the use of protective gloves is deemed necessary to avoid skin irritation. For spot cleaning, spray from a distance of 25cm. Allow for the product to act for 2-3 minutes. Following, remove the residues with a wet sponge or rinse with plenty of water. For general boat cleaning, dilute the product in a bucket with clean water, at a ratio of 1:1. Use the solution to soak the surfaces. It is recommended to use a short pile stiff broom for easy scrubbing and effective cleaning. Rinse with plenty of water before the cleaner dries on the surfaces. Caution: After the cleaner is applied on colored gel coat and sensitive surfaces, it has to be rinsed with water within the next 30 seconds.

LIMITATION OF USE

It is not recommended for cleaning brass and bronze surfaces.

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

DUROSTICK YACHT CLEANER

Strong cleaner for boats with active ingredients

CONSUMPTION

1lt/12-14m² of surface.

STORAGE

Store in shaded places for at least 36 months from production date.

SAFETY DIRECTIONS

The product is classified as corrosive. It is recommended to keep it locked, away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 18 pcs of 750ml each one 5lt, 10lt containers (special order)

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Scent	Long-lasting fresh
	scent
рН	11.0±0.5
Contains	Non-ionic surfactants are less than 5% Anionic surfactants are less than 5%, Phosphates are more than 5% but less than 15%
General Chemical State Laboratory Reg. No. 13980/0/2009 Permit No. by General Chemical State Laboratory ELEFSIS: 3093/2008	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612 THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367 E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

